



Rasant – the functional sewing thread for a wide variety of uses. Its combination of cotton covering and high-strength polyester core gives Rasant a high breaking resistance and a well-balanced elongation behaviour. In addition, especially the coarser tickets of this thread feature a high thermal resistance. All this guarantees its outstanding performance in the sewing process and in the seam.

Its specially developed finish, its high twist purity and the functional twist design assure Rasant's excellent sewability.

Rasant's outstanding qualities make it the functional sewing thread for the most versatile applications. Because of its high resistance it is especially suited for use in automated, multi-directional sewing machines.

Rasant is available in a wide range of colours, in many strengths and make-up styles – and also in a water-resistant version.



Fields of Application

TLasant 11, 15, 20, 25

The functional tickets for tarpaulins, tents, heavy fabrics, upholstered furniture, etc.

Flasant 30

The special sewing thread with polyamide core for the upholstered furniture and automotive industry.

TLasant 35

The machine-proof sewing thread for quilting seams on jeans, for upholstery, heavy work clothes and any other heavy-duty seams.





Flasant 50

The break-proof sewing thread for leather, jeans, upholstered furniture, slippers and quilting seams.

Flasant 75


The hard-wearing and machine-proof sewing thread for trousers and jeans, for work clothes, mattresses and quilts.

Flasant 120

The machine-proof and powerful sewing thread for skirts, dresses, blouses and shirts, for underwear, swimwear, jersey and knitwear. Suitable for making bedclothes, curtains and for trimming work.

Excellent sewability · machine-proof · universal

Article	Art.No.	Make-up Styles		Recommended Needles	
				Nm	Size No.
Rasant 11	0030	1.100 m	Со	160-180	23-24
Tlasant 15	0035	1.400 m	Со	140-160	22-23
Flasant 20	0040	1.500 m	Со	130-160	21-23
Flasant 25	0046	2.000 m	Со	130-160	21-23
Flasant 30	0048	2.500 m	Со	120-140	19-22
TLasant 35	01016	3.000 m	Со	110-130	18-21
Flasant 50	0051	1.000 m	XW	100-110	16-18
	00052	5.000 m	Со		
Flasant 75	0054	1.000 m	XW	90-100	14-16
	00055	5.000 m	Со		
Flasant 120	0076	1.000 m	XW	70-80	10-12
	00077	5.000 m	Со		











Amann & Söhne GmbH & Co. KG

Hauptstraße 1

74357 Bönnigheim - Germany Phone +49 7143 277-250 Fax +49 7143 277-460

nt@amann.com · www.amann.com